

MODEL : PY-  
 NET OPENING :  
 UNITS REQUIRED :  
 PYRAMID COLOR :  
 FINISH :


**SECTION VIEW - PYRAMID SKYLIGHT (PY)**

SCALE : 1/2" = 1"

**SPECIFICATIONS:**

UNIT SHALL BE CONSTRUCTED OF 6063-T5 ALUMINUM EXTRUSION HAVING MINIMUM WALL THICKNESS OF .063. UNIT SHALL BE NEATLY FORMED AND FABRICATED WITH ALL JOINTS AND SEAMS COMPLETELY WELDED BY HELI-ARC PROCESS TO ENSURE MAXIMUM STRENGTH AND WATER TIGHTNESS. ACRYLIC PLASTIC DOME SHALL BE OF A THICKNESS AND CONFIGURATION TO CONFORM WITH U.B.C. REQUIREMENTS AND AAMA SPECIFICATIONS. UNIT SHALL BE SUPPLIED TO JOB READY FOR INSTALLATION.

CALIFORNIA STATE FIRE MARSHAL APPROVAL NO. 4350-054  
 SEE I.C.B.O. ES APPROVAL NO. 1998  
 CITY OF LOS ANGELES RESEARCH REPORT NO. RR-2708

 <b>INDUSTRIAL</b> <b>LADDER &amp; SCAFFOLDING</b> <small>8152 BELVEDERE AVE SACRAMENTO, CA (916)452-0231</small>		<i>By</i> <i>Lane-Aire</i>
JOB		SHEET OF
ARCH.		
CONTR.		DWG. NO. PY SQR.
SUB. CONTR.		
DRAWN BY -		DATE: